

V-COIL

THREAD INSERT SYSTEM ■ ■ ■





VÖLKE GmbH

Morsbachtalstraße 20
D-42855 Remscheid

Telefon +49 2191 490112
Telefax +49 2191 490125

E-Mail: info@voelkel.com
Internet: www.voelkel.com

Follow us! VÖLKE on:






Thread Repair Kits V-COIL rapid

Wire Thread Inserts 1,5 D

Kit Ripristina Filetti V-COIL rapid

Filetti Riportati - tipo standard 1,5 D



						Art.-No.	€
---	---	---	---	---	---	----------	---

M

M	2.5 x 0.45	2.6 mm	08090	07090	1/4"	10	04303	21,00
M	3 x 0.5	3.2 mm	08091	07091	1/4"	10	04305	21,00
M	4 x 0.7	4.2 mm	08092	07092	1/4"	10	04307	21,50
M	5 x 0.8	5.2 mm	08093	07093	1/4"	10	04309	21,40
M	6 x 1.0	6.3 mm	08094	07094	1/4"	10	04310	23,10
M	8 x 1.25	8.3 mm	08095	07095	1/4"	10	04312	29,40
M	10 x 1.5	10.4 mm	08096	07096	1/4"	10	04316	33,00
M	12 x 1.75	12.4 mm	08097	07097	1/4"	6	04321	36,00



STI-Taps (Second Lead)

for Wire-Thread-Inserts ISO 2 (6H)


Maschi STI
per inserti riportati dopo ISO 2 (6H)



Form D HSS-G Tol. ISO1 (4H)

M

Nominal Diameter D	P	B	L1	L2	D2	∅	Art.-No.	€
M 2	x 0.40	2.5	44.5	9.5	2.8	2.24	03001	6,90
M 2.5	x 0.45	3.1	48.0	11.0	3.15	2.50	03003	6,90
M 3	x 0.5	3.6	53.0	13.0	4.0	3.15	03005	6,10
M 3.5	x 0.6	4.3	53.0	13.0	4.5	3.55	03006	6,10
M 4	x 0.7	4.9	58.0	16.0	5.0	4.00	03007	6,10
M 5	x 0.8	6.0	66.0	19.0	6.3	5.00	03008	6,10
M 6	x 1.0	7.3	72.0	22.0	8.0	6.30	03009	6,10
M 7	x 1.0	8.3	72.0	22.0	9.0	7.10	03010	7,60
M 8	x 1.25	9.6	80.0	24.0	10.0	8.00	03011	7,60
M 8	x 1.0	9.3	80.0	24.0	10.0	8.00	03012	7,60
M 9	x 1.5	11.0	85.0	25.0	8.0	6.30	03014	10,00
M 9	x 1.25	10.6	85.0	25.0	8.0	6.30	03013	9,30
M 10	x 1.5	11.9	89.0	29.0	9.0	7.10	03015	9,30
M 10	x 1.25	11.6	85.0	25.0	8.0	6.30	03016	9,30
M 10	x 1.0	11.3	85.0	25.0	8.0	6.30	03017	9,30
M 11	x 1.5	12.9	89.0	29.0	9.0	7.10	03018	10,50
M 11	x 1.25	12.6	89.0	29.0	9.0	7.10	03019	11,50
M 12	x 1.75	14.3	95.0	30.0	11.2	9.00	03020	10,50
M 12	x 1.5	14.0	95.0	30.0	11.2	9.00	03021	12,80
M 12	x 1.25	13.6	95.0	30.0	11.2	9.00	03022	12,80
M 12	x 1.0	13.3	95.0	30.0	11.2	9.00	03023	12,80
M 14	x 2.0	16.6	102.0	32.0	12.5	10.00	03027	14,60
M 14	x 1.5	16.0	102.0	32.0	12.5	10.00	03028	14,60
M 14	x 1.25	15.6	102.0	32.0	12.5	10.00	03029	14,60
M 14	x 1.0	15.3	102.0	32.0	12.5	10.00	03030	14,60
M 16	x 2.0	18.6	112.0	37.0	14.0	11.20	03033	18,40
M 16	x 1.5	18.0	104.0	29.0	14.0	11.20	03034	18,40
M 18	x 2.5	21.3	118.0	38.0	16.0	12.50	03035	23,00
M 18	x 2.0	20.6	104.0	29.0	14.0	11.20	03036	23,00
M 18	x 1.5	20.0	104.0	29.0	14.0	11.20	03037	23,00
M 20	x 2.5	23.3	118.0	38.0	16.0	12.50	03038	25,50
M 20	x 2.0	22.6	113.0	33.0	16.0	12.50	03039	25,50
M 20	x 1.5	22.0	113.0	33.0	16.0	12.50	03040	25,50
M 22	x 2.5	25.3	130.0	45.0	18.0	14.00	03041	29,40
M 22	x 2.0	24.6	120.0	35.0	18.0	14.00	03042	29,40
M 22	x 1.5	24.0	120.0	35.0	18.0	14.00	03043	29,40
M 24	x 3.0	27.9	138.0	48.0	20.0	16.00	03044	37,10
M 24	x 2.0	26.6	127.0	37.0	20.0	16.00	03045	37,10
M 24	x 1.5	26.0	120.0	35.0	18.0	14.00	03046	37,10





STI-Taps (Second Lead)

for Wire-Thread-Inserts

Maschi STI

per inserti riportati



Form D

HSS-G

[illegible]